PLM-Humidity-Temp

Erweiterungskarte für *ProfiLux*–Computer

Eigenschaften
Die Karte *PLM-Humidity-Temp* erweitert Ihren *ProfiLux* um einen Eingang zum Anschluss des kombinierten Lufttemperatur- und Luftfeuchte-Sensors *Humidity-Temp-Sensor* von GHL – es darf ausschließlich nur genau dieser Sensor angeschlossen werden!
Die Messbereiche liegen zwischen 0% und 99% rel. Luftfeuchte bzw. -40°C und 120°C.

Voraussetzungen:

- Ein freier Steckplatz im *ProfiLux*

Die Karte gemäß der *ProfiLux*-Bedienungsanleitung in einen freien Slot (Steckplatz) einstecken. Beim Wiedereinschalten erkennt *ProfiLux* automatisch die neue Karte und zeigt *HUMI & TEMP* an, danach stehen die neuen Luftfeuchte- und Lufttemperatur-Funktionen zur Verfügung.

ACHTUNG: Karte nur einstecken oder abziehen, wenn *ProfiLux* spannungslos ist – Karte so einstecken, dass der Stecker richtig (mit allen Kontakten) in der Buchse steckt - *ProfiLux* und Karte werden sonst zerstört!!!

Wichtige Hinweise:

- Den *Humidity-Temp-Sensor* niemals in einen anderen Anschluss als in den vorgesehenen Anschluss der Erweiterungskarte *PLM-Humidity-Temp* stecken!
- Den Sensor nur anschließen, wenn *ProfiLux* stromlos ist!
- Der Sensor ist nicht wasserdicht und darf daher nicht nass werden, ebenso ist kondensierende Feuchtigkeit (z.B. niederschlagender Nebel) sowie stark salzhaltige Luftfeuchtigkeit zu vermeiden! Beachten Sie dies bitte bei der Standortwahl, z.B. im Terrarium mit einer Beregnungsanlage. Gegebenenfalls platzieren Sie den Sensor an einer trockeneren und wärmeren Stelle und passen Sie die Regelungseinstellungen entsprechend an.

Garantie
Auf die Karte *PLM-Humidity-Temp* geben wir 2 Jahre Garantie, auf den Sensor geben wir eine beschränkte Garantie von 1 Jahr auf Fabrikationsmängel. Ein Sensor-Schaden aufgrund von übermäßiger Feuchtigkeit ist kein Garantiefall.
Die Nichtbeachtung dieser Anleitung oder die unsachgemäße Verwendung führt zum Verlust der Garantie!

Haftungsausschluss
Der Hersteller übernimmt keinerlei Haftung für (Folge-) Schäden die durch den Gebrauch des Artikels entstehen.

2020-04-27
GHL Advanced Technology
GmbH & Co. KG
Marie-Curie-Str. 20
67661 Kaiserslautern
www.aquariumcomputer.com

PLM-Humidity-Temp

Extension card for *ProfiLux* controller

Properties

This card extends your *ProfiLux*: One input for the combined air temperature and humidity sensor *Humidity-Temp-Sensor* from GHL – only exactly this sensor can be connected!
The measurement ranges are 0% to 99% relative humidity and -40°C to 120°C.

Requirements

- One free extension slot in *ProfiLux*

The card has to be plugged into a free slot, accordingly to the operating manual. *ProfiLux* recognizes automatically the presence of the new card and displays *HUMI & TEMP*. From there on the new air temperature and humidity functions are available.

Attention: Plug the card only when *ProfiLux* is powerless – make sure plug is correctly and completely in the socket (with all contacts) – otherwise *ProfiLux* and card will be damaged!!!

Important notes

- Never insert the plug of the *Humidity-Temp-Sensor* in another socket than the socket of this card!
- Connect the sensor when *ProfiLux* is powerless only!
- The sensor is not waterproof and therefore may not become wet, you have to avoid also condensing humidity (e.g. condensed mist) as well as a highly saline humidity! Please keep this in mind when choosing the position, e.g. in a terrarium with a sprinkling system. If necessary, place the sensor at a more dry and warmer position and adjust the regulation settings accordingly.

Warranty

We issue a warranty of 2 years for the card *PLM-Humidity-Temp* and a limited warranty of 1 year for the sensor regarding manufacturing defects. A defect of the sensor due to an excessive humidity is no warranty case.
The non-observance of this instruction or the improper use leads to a loss of warranty!

Disclaimer

The manufacturer doesn't assume any liability for (consequential) damages which are caused through the use of these products.

2020-04-27
GHL Advanced Technology
GmbH & Co. KG
Marie-Curie-Str. 20
67661 Kaiserslautern
www.aquariumcomputer.com